

S-MicroW XL Flexible

S-MicroW L Flexible is a temperature data logger from -40°C to 140°C (calibration from 25°C to 140°C) with 30 cm flexible probe and 50 mm or on demand length external probe (probes cannot be switched) on a 5 mm base (base height is not counted for probe length), managed with Windows software and USB interface (DiskInterface HS, Multibay).

The other versions of the data logger are:

- S-MicroW L: with rigid probe of different lengths
- S-MicroW L Bendable: with semi-rigid metal bendable probe and rigid probe at the end
- S-MicroW L Ultra Freeze: includes calibration points from -40°C for use also from -80°C

For each version it is available the L model too, S-MicroW L Flexible, which has same diameter but a smaller battery: less battery life but reduced size.

There are also other models of high temperature data loggers, for pressure and humidity too.

Note: if used below -30°C, battery life will be highly reduced.



Main features

- With flexible cable to reach points that requires minimum encumbrance by the device
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -40°C** (order extra calibration points)

Plus

- Extremely high accuracy and precision: with an accuracy of $\pm 0,1^{\circ}\text{C}$ these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Easy to use even in small and narrow places thanks to the flexible probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

The system

The system is made up by:

- S-MicroW XL temperature data logger
- DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

Accessories

- SPD
- TS Manager

Applications



Validation



Sterilisation



Pharmaceutical



Healthcare



Medical



Laboratories



Food & Beverages



Pasteurisation

- Tecno Calib
- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- Teflon protective tube
- S-Micro XL / S-MicroW XL heat protection 1
- S-Micro XL / S-MicroW XL heat protection 2
- S-MicroW XL battery kit

Technical specifications

Dimensions	64 h X 20 Ø (mm)
Probe dimensions	Probe base dimensions 5 h X 14 Ø (mm) - Flexible probe 300 l X 4 Ø (mm) - Rigid probe base dimensions 5 h X 5,5 Ø (mm) - Probe 50 l X 3 Ø (mm) - Probe l on demand X 3 Ø (mm) (l on demand: min. 10 mm / max. 175 mm. For longer probes ask for quotation)
Weight	69 gr
Materials	Stainless steel AISI316L, PEEK
Temperature range	-40°C ÷ +140°C
Standard calibration points (temperature)	25/50/75/100/121/140°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +140 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,1 °C (within the calibration range)
Memory (n. of acquisitions)	20.224
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+17.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS, Multibay universale