

Tinytag Input Leads

CAB-3239, CAB-3246 & CAB-3233



CAB-3239 Tinytag Voltage/Current Input Lead

For use with: TGPR-0704, TV-4704, TV-4804
TR-3703, TR-3704
TGRF-4703, TGRF-4704, TGRF-4743, TGRF-4744

Cable Length: 1.5m
Weight: 60g
Material: PVC
Temp Rating: -10 to +85°C
IP Rating: IP68 (Connector)

CONNECTION INFORMATION

Colour	Pin	Function
Red	A	DO NOT CONNECT
Green	B	N/C
White	C	Sense Line
Black	D	Common/0V
Yellow	E	Signal Input



CAB-3246 Tinytag Current, Millivolt, Count Input Lead

For use with: TGPR-0804, TGPR-1001, TGPR-1201
TR-1201, TR-3804
TGRF-4804, TGRF-4844, TGRF-4901,
TGRF-4904

Cable Length: 1.5m
Weight: 35g
Material: PVC
Temp Rating: -10 to +85°C
IP Rating: IP68 (Connector)

CONNECTION INFORMATION

Colour	Pin	Function
Blue	A	Common/0V
Red	B	Signal Input



CAB-3233 Talk Voltage/Current Input Lead

For use with: TK-4702, TK-4703, TK-4802

Cable Length: 1.5m
Weight: 27g
Material: PVC
Temp Rating: -10 to +85°C
IP Rating: IP30 (Not Waterproof)

CONNECTION INFORMATION

Colour	Jack Plug	Function
White	Tip	Sense Line
Yellow	Ring	Signal Input
Black	Shank	Common/0V

Approvals

Gemini Data Loggers (UK) Ltd. operates a Business Management System which conforms to ISO 9001 and ISO 14001.

